

Technical Requirements for
BATTERY, DRY CELL, AAA

PRODUCT SPECIFICATIONS

- Voltage: 1.5 volts
- Type: Alkaline
- No mercury and cadmium added/Mercury and Cadmium Free
- Positive polar ends must be marked
- Shelf Life: Five (5) years (min.) from date of acceptance
- With cautionary advice
- Brand and Shelf Life shall be engraved/embossed/printed on the item

EVIDENCE and VERIFICATION

- **Documentary Evidence to be submitted during Post-qualification:**
 - Material Safety Data Sheet
 - With instructions on proper handling and storage.
 - Certificate from the Manufacturer
 - Current and Valid IEC 60086 Certificate relevant to alkali batteries
 - Current and Valid ISO 9001 Certificate
- **In-House Test:**
 - Using a voltmeter/multitester, measure the battery voltage,
 - Voltage: 1.5 volts
 - Positive polar end must be marked
 - With cautionary advice
 - Shelf Life: Five (5) years (min.) from date of acceptance
 - Brand and Shelf Life shall be engraved/embossed/printed on the item
- Two (2) blister packs of two (2) pieces per blister pack with marking/labeling shall be provided by the bidder during the submission of additional post-qualification documents for verification of the product specifications.

PACKAGING

- Two (2) pieces per blister pack
Ten (10) blister packs per box.
Twenty (20) boxes per carton or Standard packaging of the manufacturer.
- Additional Requirement on Packaging, refer to the attached Annex "A"

MARKING/LABELING

- Shall conform with the minimum Marking and Labeling Requirements under Article 77 of Republic Act 7394 (Consumer Act of the Philippines) whichever is/are applicable among those requirements to this item.
- Type: Alkaline
- No mercury and cadmium added/Mercury and Cadmium Free

REFERENCES

- *PNS IEC 60086-2:2022*