

COMMON-USE SUPPLIES and EQUIPMENT

PS STANDARD No. ES 006:2014

UNSPSC Code: 39101605-FL-T02

TECHNICAL SPECIFICATIONS

FLUORESCENT LAMP, 36 watts

Linear tubular		
Diameter: T8		
Shade: Daylight/cool daylight		
Wattage Rating: 36 watts		
Voltage Range: 220-240v		
Frequency: 50-60hz		
Lamplife:13,000 hours (min.)*		
Lumen Output: 2340 (min)*		
Lamp Efficacy at 100 h (Lm/W): The minimum efficacy of a halo phosphate lamp shall not be less than the values stated in the table below:		
Input Power Lamp (w)	Initial Luminous Efficacy (lm/w)	
	Correlated Color Temperature (CCT)	
	≤ 4000K	> 4000k
≥ 36 to < 65	70	65
With PS Mark/ICC Mark printed on the item.		
* Note: should be indicated in the label		
Packaging: Twenty-five (25) tubes per box, individually wrapped in carton		

TECHNICAL SPECIFICATION REVIEW COMMITTEE:

Manuel S. Avila
ENGR. MANUEL S. AVILA
 Head, Technical Working Group

Sixto V. Antonio, Jr.
SIXTO V. ANTONIO, JR.
 Senior BAC Chairman

Julietta M. Lozano
ENGR. JULIETA M. LOZANO
 Chief, Inspection Division

Flerida G. Arias
FLERIDA G. ARIAS
 Operations Manager

Jose Tomas C. Syquia
ATTY. JOSE TOMAS C. SYQUIA
 Executive Director IV

SEPTEMBER 2014