

COMMON-USE ITEMS and EQUIPMENT

PS STANDARD No. OE 022:2014


UNSPSC Code: 43212102-PR-D02


TECHNICAL SPECIFICATIONS



PRINTER, impact, dot matrix, 24 pins

Number of columns: 136
Print Direction: Bi-directional with logic seeking
Print Speed: 480cps high speed draft 10cpi
Interface: parallel or USB
Paper Handling: Manual, tractor feeder
Mean Print Volume Between Failure (MPVBF): 24 million lines (except print head)
Mean Time Between Failures (MTBF): 20,000 power-on hours (POH) (hours at 25% duty cycle)
Black Ribbon Life: 8 million characters (approx.)
Print Head Life: 400 million strokes/wire (approx.)
Power Requirement: 220 VAC/60Hz
Accessories: Power cable, USB cable, software driver (if any), operating manual, ribbon cartridge
Product Warranty: One (1) year on parts and services
Brand shall be engraved/ embossed/ printed on the item
Brochure and/or Technical Data Sheet
Notarized Certificate of parts and consumables availability in key cities of every region issued by the manufacturer or principal
Certification of 72 hours Service Response Time upon Receipt of Complaint and List of Service Centers in Key Cities in Luzon, Visayas and Mindanao
Packaging: One (1) unit per box

TECHNICAL SPECIFICATION REVIEW COMMITTEE:


ENGR. MANUEL S. AVILA
Head, Technical Working Group


SIXTO V. ANTONIO, JR.
Senior BAC Chairman


ENGR. JULIETA M. LOZANO
Chief, Inspection Division

FLERIDA G. ARIAS
Operations Manager


ATTY. JOSE TOMAS C. SYQUIA
Executive Director IV

SEPTEMBER 2014