

COMMON-USE ITEMS and EQUIPMENT

PS STANDARD No. OS 039:2014

UNSPSC Code: 44102606-RI-T01

TECHNICAL SPECIFICATIONS

RIBBON, for Manual Typewriter


Universal spool
Nylon
Black
Width: 12.7mm-13mm
Thickness: 0.09mm-0.15mm
Length: Eight (8) meters (min)
Shall conform with the required performance test:
Durability Test:
Recuperation Test
Type Filing Test
Packaging: In box, with each spool individually wrapped in plastic [Twelve (12) spools per box]

R

PERFORMANCE TEST

- ❖ **Durability Test:** Ribbons shall have 75 lines that are of good intensity, distinct and easily legible after subjection to the durability test.
- ❖ **Recuperation Test:** The 26th line shall match the tint of the 3rd line; the 1st line shall reasonably match the 3rd line of the durability test after letting the ribbon recouped after one hour.
- ❖ **Type Filling Test:** There shall not be any evidence of filling of types when impressions taken on typewriting paper are tested under the normal travel of ribbon.

TECHNICAL SPECIFICATIONS REVIEW COMMITTEE:


ENGR. MANUEL S. AVILA
Head, Technical Working Group


SIXTO V. ANTONIO, JR.
Senior BAC Chairman


ATTY. JOSE TOMAS C. SYQUIA
Executive Director IV


ENGR. JULIETA M. LOZANO
Chief, Inspection Division


FLERIDA G. ARIAS
Operations Manager

SEPTEMBER 2014