

COMMON-USE ITEMS and EQUIPMENT

PS STANDARD No. PP 025:2014


UNSPSC Code: 14111704-TT-P01

TECHNICAL SPECIFICATIONS

TOILET TISSUE PAPER, 2 ply

Brand
Weight: 28gsm (min.)
Area = wL = 10,000 mm ²
Acidity, pH: 6 (min.)
Tensile Strength, kN/m, (min.)
MD: 0.13
CD: 0.03
60% Virgin Pulp, (min.)
Absorption time for each sheet using 0.01ml water, sec.: 30 (max)
150 pull per roll (300sheets), (min.)
Shall be evenly and firmly wound to form a roll which is sufficient rigid to withstand normal handling and usage
Roll shall be perforated across the full width such that each sheet can be easily torn off along the perforations.
Toilet tissue shall be manufactured and packed under hygienic conditions. It shall not have noticeable dust on the surface of sheets
Laboratory Test Result, if any.
Packaging: Twelve (12) rolls in a pack Eight (8) packs in a box
<i>Reference: PNS 73:2004</i>

TECHNICAL SPECIFICATIONS REVIEW COMMITTEE:



ENGR. MANUEL S. AVILA
Head, Technical Working Group


SIXTO V. ANTONIO, JR.
Senior BAC Chairman

MARCH 2015


ATTY. JOSE TOMAS C. SYQUIA
Executive Director IV


ENGR. JULIETA M. LOZANO
Chief, Inspection Division


FLERIDA G. ARIAS
Operations Manager